






ΠΙΝΑΚΑΣ ΣΥΜΒΑΤΟΤΗΤΑΣ **CRANKS**

	ROTOR 3D	ROTOR 3D^F	ROTOR 3D⁺	ROTOR FLOW	ROTOR POWER	
						
ROAD BCD OPTIONS	110, 130, 130 AERO	110, 130	110, 130, Triple Road 130, 130 MAS, 110 MAS	110 MAS, 130 MAS	130 MAS, 110 MAS	
MTB BCD OPTIONS	XC2 110/74, XC3 104/64	XC2 110/74, XC3 104/64	XC2 110/74, XC3 104/64, XC2 MAS	-	XC2 MAS	
MANUFACTURING PROCESS	CNC, lathe + mill	Forge + CNC milling	CNC milling	CNC milling	CNC milling	
AXLE DIAMETER (mm)	24	30	30	30	30	
AXLE MATERIAL	Steel	Aluminium	Aluminium	Aluminium	Aluminium	
PRELOAD ADJUSTMENT	Yes	Yes	Yes	Yes	Yes	
WEIGHT (175 mm, BCD130; W/O RINGS)	540 g	532 g	468 g / 509 g (Triple) 562 g (Aero)	563 g	527 g	
AVAILABLE ARM LENGTHS (mm) (ROAD ONLY)	165 / 170 / 172.5 / 175	170 / 172.5 / 175	150* / 155* / 160* / 165* / 170 / 172.5 / 175 / 175.5* / 180*	150* / 155* / 160* / 165* / 170 / 172.5 / 175 / 175.5* / 180*	170 / 172 / 175	
FRAME COMPATIBILITY	BBRIGHT	✓	✓	✓	✓	✓
	BB386 EVO	✓	✓	✓	✓	✓
	BB30 (68 OR 73)	✓	✓	✓	✓	✓
	PF30	✓	✓	✓	✓	✓
	BB90	✓	X	X	X	X
	BB92 (MTB) /BB89/ BB86 (ROAD)	✓	✓	✓	✓	✓
	ITA (70)	✓	✓	✓	✓	✓
	BSA (68 OR 73)	✓	✓	✓	✓	✓

* special order for these sizes